

TECHNICAL CHARACTERISTICS		PH600	PH800	PH1000	PH1200	PH1300	PH1600	PH2000	PH2500
Nominal press force	kN	600	800	1000	1200	1300	1600	2000	2500
Stroke length	mm	500	600	600	600	600	600	600	600
Working speed of the slide	mm/s	24	13	14	13	12	11	9	9
Forward speed of the slide	mm/s	310	110	260	270	270	350	300	300
Backward speed of the slide	mm/s	300	270	380	270	270	400	300	300
Distance table – slide	mm	800	800	800	800	800	800	800	800
Throat depth (C-frame depth)	mm	320	360	360	360	360	360	370	370
Bolster plate dimensions	mm	800	1000	1000	1000	1000	1000	1400	1400
		600	700	700	700	700	700	700	700
Slide dimensions	mm	630	1000	1000	1000	1000	1000	1100	1100
		450	600	600	600	600	600	600	600
Motor power	kW	15	18,5	18,5	18,5	18,5	22	30	37
Overall dimensions	mm	1020	1020	1040	1070	1260	1400	1820	1820
		1700	1700	1980	1990	2140	2005	2220	2220
		2950	3250	3775	3450	3775	3765	3930	3930
Net weight	kg	5300	7200	10500	11000	11500	14000	16500	17100
Oil tank capacity	l	500	600	490	460	490	490	490	550
Die cushion force	mm	-	400	400	500	600	600	600	600
Die cushion stroke	mm	-	250	250	250	300	300	300	300
Die cushion table	mm	-	-	600	600	600	600	600	600
		-	-	450	450	450	450	450	450

